Inflator XGT®

MP001G

40Vmax • 11,1 bar • 161 psi

Powerful XGT® air pump for example filling tyres for cars and bicycles.

MP001G 40Vmax XGT® air pump automatically stops inflating when the preselected air pressure level is reached. Includes several valves for filling different types of products - eg footballs, tyres, etc.

XGT

Technical specifications

Nominal Battery Voltage	40 V
Voltage XGT	✓
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Maximum Flow Rate	24 L/min
Max Pressure	11,1 bar
Hose length	0,65 m
Sound Pressure Level (L_{pA})	74 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level (3 axes)	3,8 m/s²
Vibration Uncertainty (K Factor)	1,5 m/s²
Tool weight with battery	2,9 - 4,1 kg
Product net weight	2,2 kg
Product Dimensions (L x W x H):	329 x 108 x 231 mm

User benefits

- Excess air can be released by pressing and holding the air release button
- The machine stops automatically when target pressure is reached
- 3 Inflation modes (High speed, Low speed or Ball modes)
- The machine remembers the pressure setting last time you power off
- eXtreme Protection Technology (XPT) is engineered for improved dust and water resistance for operation in harsh conditions
- LED job light for easy operation in the dark
- Thermostat protects the machine from overheating
- Ergonomic soft grip handle provides increased comfort
- Battery protection circuit protects against overloading, over-discharging and over-heating
- Increased air discharge amount drastically shortens the time to inflate large tyres of tractors, trucks, and more
- Digital pressure gauge with backlight for increased

Link to product - www.makitauk.com

Related products

Optional AC

TE00000333
Swim Ring Adapter

TE00000334
French Adapter

TE00000346
Dunlop Adapter

TE00000592
Ball Adapter

Other

User manual

Parts drawing